

Tiandy



TC-R3820 Spec: I/F/N

H.265 8HDD 20ch Face Recognition NVR

AI Series



KEY FEATURES

HD Input

- S+265/H.265/H.264 video compression
- Connectable to the third-party network cameras
- Up to 20-channel input
- Supports live view, storage, and playback of the connected camera at up to 12MP resolution

HD Output

- HDMI and VGA independent outputs
- HDMI Video output at up to 4K (3840 × 2160) resolution

HD Storage

- 8 SATA interfaces, up to 10TB for each HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%

HD Transmission

- 2 self-adaptive 10/100/1000 Mbps network interface

Various Applications

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.
- 1:N face recognition.
- Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- Web6 supports plug-in-free browsing; and can preview videos on all browsers"




SPECIFICATIONS

Input	
Video Input	20-ch
Max Resolution	12MP
Two-way Audio Input	1-ch, 3.5mm
Bandwidth	Income 400Mbps; Outcome 200Mbps
Output	
HDMI/VGA Output	HDMI: 2-ch, 3840×2160, 2560×1600, 2560×1440, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800 VGA:2-ch, 1920×1080, 1280×720, 800×600, 1024×768, 1366×768, 1440×900, 1280×800
Screen Split	1/3/4/6/8/9/10/13/16/20/25
Audio Output	1×3.5mm, 1×BNC
Decoding	
Decoding Format	S+265H.265/H.264
Recording Resolution	12MP/8MP/5MP/4MP/1080p/960p/720p/D1/2CIF/CIF
Preview Capability	2×12MP, 3×4K, 5×5MP, 7×4MP, 15×1080P, 30×720P, 20×4CIF
Synchronous Playback	2×12MP, 3×4K, 5×5MP, 7×4MP, 15×1080P, 16×720P
Records Encryption	Yes
Hard Disk	
SATA	8 SATA interfaces for 8 HDDs
Capacity	Up to 10TB for each HDD
eSATA Interface	1 SATA interface
Array Type	JBOD,RAID0/1/5/10
External Interface	
Network Interface	2×RJ45 self-adaptive 10/100/1000 Mbps network interfaces
USB Interface	2×USB 2.0, 1×USB 3.0
Serial Interface	2×RS485, 1×RS232
Alarm In/Out	16/4
Reliability	
N+M Hot Standby	Yes
ANR	Yes
Face Recognition	
Base Libraries	32
Face Pictures	50,000
Video Stream for Recognition	8
Picture Stream for Recognition	16
Face Picture Search	Yes
General	
Web Version	Web6
Language	English, Simple Chinese
Operating Conditions	-10°C ~ 55°C, 10%~90% RH
Power Supply	AC100~240V , 50/60HZ
Consumption (without HDD)	≤100W (without HDD)
Chassis	2U
Dimensions	94×440×460 mm (3.7×17.32×18.11 inch)
Weight (without HDD)	7.2Kg (15.87lb)

AVAILABLE MODEL

TC-R3820 SPEC: I/F/N

DIMENSIONS (Unit: mm)



Physical Interfaces

